



MASTER PRICE SHEET



This list supersedes all previous lists.

USA MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-520 Rotary Cutter

SPECIFICATIONS

- | | | |
|---|---|--|
| - Overall Width --- 247" (6.2m) | - Transport Width --- 91" (2.32m) | - Min. Tractor Size --- 100hp (75kw) |
| - Overall Length --- 242" (6.15m) | - Transport Height --- 120" (3.05m) | - Blade Tip Speed --- 16,000 ft/min |
| - Cutting Height --- 2" - 17.5"
(Depending on Tire Size) | - Cutting Capacity --- 2" (51mm)
2" (51mm) Fixed Knife | - Blade Overlap --- 6" (153mm) |
| - Cutting Width --- 240" (6.10m) | 4" (102 mm) Pan Unit | - Deck Thickness --- 180" (7 ga) (4.6mm) |

HOW TO ORDER: You must select from 1 - 6 to receive a complete rotary cutter including standard features. To receive additional options, choose from selection 7.

~ ~ Selection 1 ~ Choose a Basic Unit ~ ~

		Price USA	Wt/lbs
1)	C520-100 Basic 20' Unit, 1000 RPM	31,270.00	5,221
2)	S000-080 Safety Light Kit (Required)	410.00	

~ ~ Selection 2 ~ Choose a Hitch Type and Accessories ~ ~

2)	C520-170	Trailing hitch, CV Style	1,080.00	179
	Choose a Clevis:			
	a)	C502-113WG Solid Tongue	114.00	13
	b)	C502-107WG Open Clevis	101.00	12
	c)	C000-300WG Precision hitch	413.00	29
	d)	C000-360WG Adjustable Hitch	279.00	
	e)	C502-816WG Solid Tongue with 2-3/16" hole for 2" pin	126.00	
	f)	C502-815WG Clevis with 2 3/16" Opening	129.00	13
	Choose a Tractor Shaft:			
	a)	340-8082WG CV Shaft, 1 3/4 x 20 Spline	1,641.00	79
	b)	340-8092WG CV Shaft, 1 3/8" x 21 Spline	1,641.00	79
3)	C520-180	Parallel Ring hitch (For European Applications Only)	1,309.00	217
	a)	340-5515WG Shaft, 1 3/8" x 6 with Over-Running Clutch	1,392.00	79
4)	C520-175	High hitch (For Germany Only)	1,430.00	262
	Choose a Tractor Shaft:			
	a)	340-5510AWG CV Shaft, 1 3/8" x 21 Spline	1,171.00	79
	b)	340-5511AWG CV Shaft, 1 3/4" x 20 Spline	1,171.00	79

Assembly charge on pan units Net 550.00

Assembly charge on fixed blade units Net 650.00

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEET

This list supersedes all previous lists.




USA MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017



FX-520 Rotary Cutter



Price USA Wt/lbs

~ ~ Selection 3 ~ Choose a Blade Configuration ~ ~

1)	C520-250	Pan Kit with Updraft Blades and Shrouds	2,693.00	624
2)	C520-260	Pan Kit with Shredder Blades and Shrouds	3,061.00	761
3)	C520-265	Fixed Knife Shredder Kit with Updraft Blades & Shrouds	4,252.00	965
4)	C520-295	Fixed Knife Cotton Kit with Flat Blades & Shrouds	4,042.00	981

~ ~ Selection 4 ~ Choose a Safety Guard and Accessories ~ ~

1)	C520-500	Single chains front and rear	1,085.00	340
a)	C520-580	Half Length Front Belting <i>(Must be used with a chain option)</i>	235.00	31
2)	C520-550	Double chains front and rear	1,355.00	677
a)	C520-580	Half Length Front Belting <i>(Must be used with a chain option)</i>	235.00	31

IMPORTANT: OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown

~ ~ Selection 5 ~ Choose Axle Option ~ ~

1)	C520-612	Standard 318 Axle kit <i>(Choose 4 Tires)</i>	3,348.00	
2)	C520-614	517 Axle Kit c/w Center duals <i>(choose 6 Tires)</i>	3,530.00	
3)	C520-616	517 Axle Kit c/w Center Walking <i>(choose 6 Tires)</i>	3,910.00	
4)	C520-618	517 Dual Axle Kit <i>(Choose 8 Tires)</i>	4,030.00	
5)	C520-622	517 Walking Axle kit <i>(Choose 8 Tires)</i>	4,790.00	
6)	C520-624	517 Center Walking Axle c/w Duals on Wings <i>(Choose 8 Tires)</i>	4,409.00	

~ ~ Selection 5 ~ Choose Tire Option ~ ~

7)	210-530WG	Tire Assembly 11L Stubble Proof <i>(Choose quantity of tires needed 6 or 8)</i>	358.00	
8)	210-182NRWG	Used Aircraft Tire <i>(Choose quantity of tires needed 6 or 8)</i>	297.00	
9)	210-505WG	Light Truck Tire <i>(Choose quantity of tires needed 6 or 8)</i>	240.00	

Prices and specifications subject to change without notice or obligation.

MASTER PRICE SHEET

This list supersedes all previous lists.



USA MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-520 Rotary Cutter

Price USA Wt/lbs

~ ~ Selection 7 ~ Choose a Destination Code ~ ~

1)	C520-NA	North America and Australia Destination Kit	58.00
2)	C520-UK	United Kingdom Destination Kit	56.00
3)	C520-FR	France Destination Kit	70.00
5)	C520-DE	Germany Destination Kit	56.00
6)	C520-RU	Russia Destination Kit	56.00
7)	C520-UA	Ukraine Destination Kit	56.00

~ ~ Selection 8 ~ Schulte Fan Kit ~ ~

1)	C520-780	Fan Debris Kit, <i>Factory Installed</i>	6,437.00
2)	C520-790	Fan Debris Kit, <i>Crated</i>	6,251.00

~ ~ Selection 9 ~ Extra Options ~ ~

2)	C520-920	Crop Dividers	235.00	35
----	----------	---------------	--------	----

IMPORTANT: When moving equipment on any type of road, if the rotary cutter obscures the tractor warning or tail lights, the cutter must be equipped with the **S000-080 Safety Light Kit**

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER



This list supersedes all previous lists.

USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-318 Pan Unit ROTARY CUTTER

CUTTER FEATURES

- North America's First 18' Flex Wing Mower
- 540/1000 RPM 80° CV Drive
- Replaceable Skid Shoes
- 7 ga Single Domed Deck and Stump Jumpers
- Rubber 3 Puck Grommet Suspension
- 90 HP Recommended Tractor
- Cutting Width 216" (5.5m)
- 540 Equal angle non cv drive
- Height Control Cylinder & Hoses
- Wing Lift Cylinders & Hoses
- 1.75" to 16.75" (44.5mm to 425mm) Cutting Height
- Operator's and Parts Manual Holder
- Over Center Folding Wings
- Transport Width (max with duals on wings) 96"(2.4m)

more specs on brochure

~ ~ Selection 1 ~ Choose a Basic Unit, Drive Package ~ ~

		<u>Price USA</u>	<u>WT(lbs)</u>
C318-100	Schulte FX-318, Basic Unit	12,179.00	5,593
S000-085	Safety Light Kit (Required)	384.00	30
Choose a Drive Package:			
a)	C318-735 Drive Package, CW Center, 540 RPM	4,930.00	in base
b)	C318-720 Precision hitch	4,930.00	in base

~ ~ Selection 2 Trailing Hitch ~ ~

Note: If using Equal Angle Hitch Skip to Selection 3

C185-195	Trailing Hitch, CV Style Required	722.00	204
Choose a CV Shaft:			
a)	340-870WG CV Shaft, 540 RPM	1,124.00	74
b)	340-648WG CV Shaft, 44E tractor Shaft 1-3/8 Z21 - 1000 RPM	921.00	60
c)	340-658WG CV Shaft, 44E tractor Shaft 1-3/4 Z20 - 1000 RPM	1,221.00	60
Choose a Clevis:			
CS01-106WG	Open Clevis (Minimum Requirments)	128.00	11
C000-360WG	Adjustable Clevis	279.00	15
C000-300WG	Precision hitch	413.00	28
C502-113WG	Solid Tongue	114.00	13

~ ~ Selection 3 ~ Equal Angle Hitch ~ ~

C185-196	Equal Angle Hitch Kit w/ 540 RPM Shaft c/w Non CV Drive Shaft	2,044.00	250
-----------------	---	-----------------	------------

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

Prices and specifications subject to change without notice or obligation.



This list supersedes all previous lists.

USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-318 Pan Unit ROTARY CUTTER

~ ~ Selection 4 ~ Choose a Chain Guards ~ ~

C318-500	Chain Guards Single Front and Rear	815.00
C318-550	Chain Guards Double Front and Rear	1,154.00
C318-560	Front Half Belting <i>(Must be used with a chain option)</i>	279.00
C318-570	Rear Half Belting <i>(Must be used with a chain option)</i>	318.00
C318-580	Front Full Belting	335.00
C318-590	Rear Full Belting	360.00

~ ~ Selection 5 ~ Choose a Pan Kit ~ ~

C318-450	Pan Kit (required)	1,605.00
----------	--------------------	----------

~ ~ Selection 6 ~ Choose a Blade Configuration ~ ~

C318-460	Updraft Blades, CW Center	290.00
C318-470	Shredder Blades, CW Center <i>(optional)</i>	464.00

~ ~ Selection 7 ~ Choose a Both Wheel Standard Kits ~ ~

C318-870	Wing Wheel Standard, 1 or 2 Tires <i>Required</i>	1,457.00	
C180-115	Dual Wheel Standard on the Center <i>Required</i>	1,124.00	237

~ ~ Selection 8 ~ Choose a Axle Kit ~ ~

C180-484	Axle Kit for 4 Tires	529.00	66
C180-486	Axle Kit for 6 Tires	793.00	99
C180-488	Axle Kit for 8 Tires	1,058.00	132

~ ~ Selection 9 ~ Choose a Tire Option ~ ~

Please state the quantity of tires that you would like to order as the numbers listed below are single tires and not tire kits.

210-003WG	Solid Laminated Tires, 6 x 9 x 20	200.00	70
210-175WG	Forklift Tire 6.5 x 10 - 10 ply on 2 pce 5 bolt rim	278.00	40
210-540WG	Tire 24x8-14 20 Ply Severe Duty	343.00	70
210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	496.00	

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEET



This list supersedes all previous lists.

USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-318 Pan Unit ROTARY CUTTER

~ ~ Selection 10 ~ Choose a Destination Code ~ ~

C318-NA	North American & Australian Decal Kit	35.00
----------------	---------------------------------------	--------------

~ ~ Selection 11 ~ Choose Extra Options ~ ~

C185-310	Independent Wing Lift	163.00
-----------------	-----------------------	---------------

	Assembly Charge	300.00
--	-----------------	---------------

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

IMPORTANT:

- 1) Safety Chain Kit must be used at all times when moving equipment on any type of road.
- 2) OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown Object Shield Message in the Rotary Cutter Spec section in sales price book.

Prices and specifications subject to change without notice or obligation.



This list supersedes all previous lists.

MASTER PRICE SHEETS



USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-315 ROTARY CUTTER

STANDARD & OPTIONAL CUTTER FEATURES

- | | | |
|----------------------------------|----------------------------------|--|
| - 7GA deck | - Residue distribution tailboard | - Replaceable deck protection rings |
| - Transport width of 99" | - Variable position shrouding | - Single domed, sweep clean deck |
| - 4 gearbox drive layout | - Fixed knife technology | - Two piece replaceable skid shoes |
| - Optional belting front or rear | - Category 5 & 6 drivelines | - Pentagon blade bolt design |
| - Hyd Phasing lift system | - Rubber suspension - standard | - Optional dbl safety chains front or rear |
| - 517 Hubs and axles | - Speed levelling system | - Full floating front hitch |

HOW TO ORDER: You must select from 1 - 8 to receive a complete rotary cutter including standard features. To receive additional options, choose from selection 9.

~~ Selection 1 ~ Choose a Basic Unit, Drive Package & Back Beam ~~

	Price USA	Wt/lbs
1) C316-100 FX-315 Rotary Cutter	15,123.00	3,630
2) S000-095 Safety Light Kit (Required)	408.00	
a) C306-705 Drive Package, CW Center, 540 RPM	4,992.00	
b) C306-715 Drive Package, CW Center, 1000 RPM	4,992.00	

Must Choose the Center Back Beam

1) C316-115 Standard Back Beam	1,457.00	222
--------------------------------	----------	-----

~~ Selection 2 ~ Choose a Hitch Type and Accessories ~~

1) C316-180 Trailing CV hitch Kit	856.00	139
Choose a Clevis:		
a) CS01-106WG Open Clevis	128.00	11
b) C000-360WG Adjustable Clevis (Not Required with FLX15 or FLX10)	279.00	15
c) C000-300WG Precision hitch	413.00	29
d) C502-113WG Solid Tongue (Not Required with FLX15 or FLX10)	114.00	13
e) C502-815WG Clevis with 2 3/16" Opening	129.00	13
Choose a Tractor Shaft:		
a) 340-870WG CV Shaft, 540 RPM	1,124.00	75
b) 340-648WG CV Shaft, 1000 RPM	921.00	62
2) C316-185 Equal Angle Non-CV hitch Kit w/ 540 RPM Shaft	2,198.00	260
3) C316-196 Parallel Ring hitch	1,195.00	224
a) 230-015WG Pintle Ring, Forged, PT-48 (installed on Parallel hitch)	125.00	
Choose Tractor Shaft		
b) 340-648WG CV Shaft, 1000 RPM	921.00	60
4) C316-195 German high hitch	1,561.00	270
a) 230-015WG Pintle Ring, Forged, PT-48 (installed on Parallel hitch)	125.00	
Choose Tractor Shaft		
b) 340-648WG CV Shaft, 1000 RPM	921.00	62

Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEETS

This list supersedes all previous lists.



USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017



FX-315 ROTARY CUTTER



~ ~ ***Selection 3 ~ Choose a Skid ~ ~***

		Price USA	Wt/lbs
1)	C316-215 Regular Skids	216.00	15

~ ~ ***Selection 4 ~ Choose a Safety Guard Kit ~ ~***

1)	C316-500	Chain Guards Double Front	NOTE: Any combination of chains & belting can be used	722.00	280
2)	C316-510	Chain Guards Double Rear		633.00	202
3)	C316-550	Full Front Belting	NOTE: When ordering Residue Distribution Tailboard NO rear guards are needed	363.00	112
4)	C316-560	Full Rear Belting		256.00	88
5)	C316-320	Residue Distribution Tailboard		2,235.00	323
	Recommended with C316-460				

IMPORTANT: Safety Tow Chain Kit must be used at all times when moving equipment on any type of road.

IMPORTANT: OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown ObjectShield Information Message in the Rotary Cutter Spec Section in the sales price book.



MASTER PRICE SHEETS



This list supersedes all previous lists.

Effective July 2, 2017

USA

MACHINE PRICES AND SPECIFICATIONS



FX-315 ROTARY CUTTER



~ ~ Selection 5 ~ Choose Pan Kit or Fixed Knife Blade Configuration ~ ~

		Price USA	Wt/lbs
1)	C316-450 Pan Kit	1,220.00	123
	Choose a blade configuration		
a)	C316-451 Updraft Blades, CW Center	286.00	35
b)	C316-453 Shredder Blades, CW Center	485.00	64
	Optional		
a)	C316-455 Bolt-On Deck Ring Option for Pan Kit	635.00	113
2)	C316-460 Fixed Knife Bars, Blades (Updraft), Mounts, CW Rotation on Center	1,993.00	213
3)	C316-220 Variable Position Shrouding (recommended with C316-460)	927.00	64

~ ~ Selection 6 ~ Choose An Axle Kit ~ ~

1)	C316-484 Axle Kit for 4 Tires	594.00	36
2)	C316-486 Axle Kit for 6 Tires	1,154.00	50
3)	C316-488 Axle Kit for 8 Tires	1,735.00	66

~ ~ Selection 7 ~ Choose A Tire Option ~ ~

1)	210-003WG Solid Laminated Tire, 6 x 9 x 20	200.00	28
2)	210-540WG Tire 24x8-14 20 Ply Severe Duty	343.00	32
3)	210-540FWG Tire 24x8-14 20 Ply Severe Duty Foam Filled	496.00	
4)	210-175WG Tire Assy, Forklift, 6.50x10-10 Ply Rated on 2pce 5 Bolt Rim	278.00	18

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEETS



This list supersedes all previous lists.

USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017



FX315 ROTARY CUTTER



~ ~ **Selection 8 ~ Choose a Destination Code** ~ ~

Please select the destination of the cutter for proper Decals, Manuals and CE Shielding Upgrade.

	Price USA	Wt/lbs
1) C316-NA North American English Destination Kit	412.00	
2) C316-FR France Destination Kit	519.00	
3) C316-DE German Destination Kit	505.00	

~ ~ **Selection 9 ~ Extra Options** ~ ~

1) C316-200 Chock Blocks	250.00	50
2) S000-095 Safety Light Kit	408.00	31
3) C316-205 Light Mount Plates, France	45.00	13

IMPORTANT: When moving equipment on any type of road, if the rotary cutter obscures the tractor warning or tail lights, the cutter must be equipped with the **S000-095 Safety Light Kit**

Assembly Charge

300.00

OPTIONAL PDI INCLUDES: greasing of all pivot points, gearbox oil checked, charge hydraulic cylinders and install pioneer ends. Tires will be installed where necessary. It is the dealers responsibility to remove shipping brackets & banding as well as to adjust mower height as specified in the operators manual. Please go to the Schulte website/dealer access for further information.

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEETS

This list supersedes all previous lists.



USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017



XH1500 Series 4 Rotary Cutter

CUTTER FEATURES

- | | | |
|-------------------------------------|----------------------------------|--|
| - 7GA deck | - Single domed, sweep clean deck | - S000-010 safety chain kit 1/4" grade 70 with 10,000 lbs capacity |
| - Two piece replaceable skid shoes | - Rubber suspension - standard | - 1/4" Round skid pans (Stump Jumpers) c/w 6 updraft blades |
| - Double safety chains front & rear | - Four gearbox drive layout | - Pentagon blade bolt design |
| - Walking axles on center section | 210hp down, 260hp splitter | - Operator's manual in holder |
| - Hydraulic phasing lift system | - Full floating front hitch | |
| - Hydraulic wing lift system | - Inboard rotation | |
| - 517 Hubs and axles | - Deck protection rings | |

HOW TO ORDER: You must select from 1 - 7 to receive a complete rotary cutter including standard features. To receive additional options, choose from selection 7.

~ ~ Selection 1 ~ Choose a Basic Unit and Drive Package ~ ~

		Price USA	Wt/lbs
1)	C308-100 Basic 15' Unit , S000-085 required in North America, but needed with FLX-151	18,577.00	4,795
2)	S000-085 Safety Light Kit (Required)	384.00	
	Choose a Drive Package:		
a)	C308-705 CW Rotation on Center, 540 RPM	4,852.00	
b)	C308-715 CW Rotation on Center, 540 RPM	4,852.00	
c)	C308-700 CCW Rotation on Center, 1000 RPM	4,852.00	
d)	C308-710 CCW Rotation on Center, 1000 RPM	4,852.00	

~ ~ Selection 2 ~ Choose a Hitch Type and Accessories ~ ~

1)	C308-195 Trailing Hitch CV Style	989.00	138
	Choose a Clevis:		
a)	CS01-106WG Open Clevis (Minimum Requirement)	128.00	12
b)	C000-360WG Adjustable Clevis	279.00	15
c)	C000-300WG Precision Clevis (not required with FLX-1510)	413.00	29
d)	C502-113WG Solid tongue (not required with FLX-1510)	114.00	13
e)	C502-815WG Clevis 2 3/16 " opening	129.00	13
	Choose a Tractor Shaft:		
a)	340-870WG CV Shaft, 540 rpm	1,124.00	77
b)	340-648WG CV Shaft, 1000 rpm	921.00	60
c)	340-658WG CV Shaft 1000 RPM 1 3/4" shaft	1,221.00	
2)	C306-196 Trailing Equal Angl Hitch c/w 540 Tractor Shaft (Not Available with FLX-1510)	2,248.00	260

Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEETS

This list supersedes all previous lists.



USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

XH1500 Series 4 Rotary Cutter

~ ~ Selection 3 ~ Choose a Blade Configuration ~ ~

		Price USA	Wt/lbs
1)	C308-450 2 Blade Pan Kit - cw Schulte Super Suction Updraft 4" Blades	1,655.00	400
2)	C308-451 2 Blade Pan Kit - ccw Schulte Super Suction Updraft 4" Blades	1,655.00	
3)	C308-452 2 Blade Pan Kit - cw Basic Suction Updraft 4" Blades	1,655.00	
4)	C308-453 2 Blade Pan Kit - ccw Basic Suction Updraft 4" Blades	1,655.00	
5)	C308-454 2 Blade Pan Kit - Bush Blades Non Updraft	1,755.00	
6)	C308-455 2 Blade Pan Kit - cw Schulte Super Suction Updraft 5" Blades	1,795.00	
7)	C308-456 2 Blade Pan Kit - cw Schulte Super Suction Updraft 5" Blades	1,795.00	

~ ~ Selection 4 ~ Choose a Wing Axle Kit ~ ~

1)	C308-870 Single Axles for Wings (6 Tires required)	1,476.00	161
2)	C308-875 Walking Axles for Wings (8 Tires Required)	2,481.00	315

~ ~ Selection 5 ~ Choose a Tire Option ~ ~

Please state the quantity of tires that you would like to order as the numbers listed below are just single tires and not a tire kit.

		Price USA	Wt/lbs
		PRICE PER TIRE	
1)	210-003WG Solid Laminated Tire, 6 x 9 x 20	200.00	70
2)	210-540WG Tire 24x8-14 20 Ply Severe Duty	343.00	70
3)	210-540FWG Tire 24x8-14 20 Ply Severe Duty Foamed Filled	496.00	
4)	210-175WG Forklift Tire 6.5x10 - 10 Ply Rated	278.00	18

~ ~ Selection 6 ~ Choose a Destination Package ~ ~

Please select the destination of the cutter for proper Decals, Manuals, and Shielding

1)	C308-NA North American/ Australia Destination Kits	410.00
----	---	---------------



MASTER PRICE SHEETS

This list supersedes all previous lists.



USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

XH1500 Series 4 Rotary Cutter

~ ~ Selection 7 ~ Extra Options ~ ~

	Price USA	Wt/lbs
1) C306-300 Manual Winch Kit	695.00	115
2) C306-320 Towing Hitch Kit	383.00	66
3) C306-805 Three Spool Valve Kit (For tractors with limited remote outlets)	1,371.00	77
4) C306-815 Double Acting Cylinder Kit "TEE" Connection	246.00	4
5) C301-830 Hydraulic Hose Ends Kit (Pioneer Ends)	67.00	3
6) C306-835 Independent Double Acting Cylinder Kit	139.00	12
7) C306-840 Extra Long Hoses for Spool Valve Kit	460.00	48
8) C306-880 Right Wing Gauge Wheel Kit	598.00	100
9) C306-885 Left Wing Gauge Wheel Kit	598.00	100
10) C306-315 Tool Box Kit	636.00	33
11) C306-305 Flex Arm Mount	165.00	0
12) C308-890 Tire Bumper Kit	483.00	

Assembly Charge

300.00

OPTIONAL PDI INCLUDES: greasing of all pivot points, gearbox oil checked, charge hydraulic cylinders and install pioneer ends. Tires will be installed where necessary. It is the dealers responsibility to remove shipping brackets & banding as well as to adjust mower height as specified in the operators manual. Please go to the Schulte website/dealer access for further information.

IMPORTANT: When moving equipment on any type of road, if the rotary cutter obscures the tractor warning or tail lights, the cutter must be equipped with the **S000-085 Safety Light Kit**

HYDRAULIC REQUIREMENTS FOR XH1500

A three circuit system provides independent lifting of each wing and height adjustment control, with float on two circuits.

This system is preferred for optimum performance.

If a three circuit system three spool valve kit is required - part #C306-805.

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER



MASTER PRICE SHEET

This list supersedes all previous lists.



USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

XH1000 Series 4 Rotary Cutter

CUTTER FEATURES

- | | | |
|-------------------------------------|----------------------------------|--|
| - 7GA deck | - Single domed, sweep clean deck | - S000-010 safety chain kit 1/4" grade 70 with 10,000 lbs capacity |
| - Two piece replaceable skid shoes | - Rubber suspension - standard | - 1/4" Round skid pans (Stump Jumpers) c/w 6 updraft blades |
| - Double safety chains front & rear | - Four gearbox drive layout | - Pentagon blade bolt design |
| - Walking axles on center section | 190hp down, 260hp splitter | - Operator's manual in holder |
| - Hydraulic phasing lift system | - Full floating front hitch | |
| - Hydraulic wing lift system | - Inboard rotation | |
| - 517 Hubs and axles | - Deck protection rings | |

HOW TO ORDER: You must select from 1 - 6 to receive a complete rotary cutter including standard features. To receive additional options, choose from selection 7.

~ ~ Selection 1 ~ Choose a Basic Unit and Drive Package ~ ~

	Price USA	Wt/lbs
1) C309-100 Basic 10' Unit	17,496.00	4656
2) S000-085 Safety Light Kit (Required)	384.00	
Choose a Drive Package:		
a) C309-700 CW Rotation on Center, 540 RPM, (Std. Rotation)	3,500.00	
b) C309-710 CW Rotation on Center, 1000 RPM (Std. Rotation)	3,500.00	
c) C309-705 CCW Rotation on Center, 540 RPM (Non Std. Rotation)	3,500.00	
d) C309-715 CCW Rotation on Center, 1000 RPM (Non Std. Rotation)	3,500.00	

~ ~ Selection 2 ~ Choose a Hitch Type and Accessories ~ ~

1) C306-195 Trailing Hitch CV Style	905.00	138
Choose a Clevis:		
a) CS01-106WG Open Clevis (Minimum Requirement)	128.00	12
b) C000-360WG Adjustable Clevis	279.00	15
c) C000-300WG Precision Hitch (Not Required with FLX1510)	413.00	29
d) C502-113WG Solid Tongue (Not Required with FLX1510)	114.00	13
e) C502-815WG Clevis with 2 3/16" Opening	129.00	13
Choose a Tractor Shaft:		
a) 340-870WG CV Shaft, 540 RPM	1,124.00	77
b) 340-648WG CV Shaft, 1000 RPM	921.00	60
2) C308-195 Trailing Equal Angle Hitch c/w 540 Tractor Shaft (Not Available with FLX1510)	989.00	260

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEET

This list supersedes all previous lists.



USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017



XH1000 Series 4 Rotary Cutter

~ ~ Selection 3 ~ Choose a Blade Configuration ~ ~

		Price USA	Wt/lbs
1)	C309-450 2 Blade Pan kit - CW Schulte Super Suction Updraft 4" Blades	1,149.00	264
2)	C309-451 2 Blade Pan kit - CCW Schulte Super Suction Updraft 4" Blades	1,149.00	86
3)	C309-455 2 Blade Pan kit - CW Schulte Super Suction Updraft 5" Blades	1,245.00	
4)	C309-456 2 Blade Pan kit - CW Schulte Super Suction Updraft 5" Blades	1,229.00	

~ ~ Selection 4 ~ Choose a Wing Axle Kit ~ ~

1)	C309-870 Single Axle Kit for Right Wing	740.00	81
2)	C309-875 Wing Walking Axle Kit for Right Wing	1,244.00	158

~ ~ Selection 5 ~ Choose a Tire Option ~ ~

Please state the quantity of tires that you would like to order as the numbers listed below are single tires and not tire kits.

		PRICE PER TIRE	
1)	210-003WG Solid Laminated Tire, 6 x 9 x 20	200.00	70
2)	210-520WG Tire 24x8-14 20 Ply Severe Duty	416.00	70
3)	210-520FWG Tire 24x8-14 20 Ply Severe Duty Foam Filled	560.00	
4)	210-175WG Forklift Tire 6.5x10 - 10 Ply Rated	278.00	18

~ ~ Selection 6 ~ Choose a Destination Code ~ ~

C309-NA	North American/ Australia Destination Kits	411.00
----------------	--	---------------

~ ~ Selection 7 ~ Extra Options ~ ~

1)	C306-300 Manual Winch	695.00	125
2)	C306-320 Towing Hitch Kit	383.00	0
3)	C306-805 Three Spool Valve Kit	1,371.00	0
4)	C306-880 Right Wing Guage Wheel Kit	598.00	32
5)	C306-315 Tool Box Kit	636.00	30
6)	C306-305 Flex Arm Kit	165.00	72

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEETS

This list supersedes all previous lists.



USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017



XH1000 Series 4 Rotary Cutter



IMPORTANT: Safety Tow Chain Kit must be used at all times when moving equipment on any type of road.

IMPORTANT: When moving equipment on any type of road, if the rotary cutter obscures the tractor warning or tail lights, the cutter must be equipped with the **S000-085 Safety Light Kit**

Assembly Charge

200.00

OPTIONAL PDI INCLUDES: greasing of all pivot points, gearbox oil checked, charge hydraulic cylinders and install pioneer ends. Tires will be installed where necessary. It is the dealers responsibility to remove shipping brackets & banding as well as to adjust mower height as specified in the operators manual. Please go to the Schulte website/dealer access for further information.

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEET



This list supersedes all previous lists.

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-1800 Pan ROTARY CUTTER

CUTTER FEATURES

- 540/1000 RPM Drive
- 7 ga. Spun Formed Stump Jumpers
- Replaceable Skid Shoes
- 7 ga Single Domed Deck
- Deck Protection Rings
- Weasler Drive Lines with Self Adjusting Clutches
- Cutting Width 180" (4.57m)
- 80 Degree CV Drive
- Height Control Cylinder & Hoses
- Wing Lift Cylinders & Hoses
- S000-010 Safety Chain (1/4" gr.70 - 10000lbs cap.)
- Operator's and Parts Manual Holder
- Over Center Folding Wings
- Transport Width (max with duals on wings) 102"(2.59m)

more specs on brochure

~ ~ Selection 1 ~ Choose a Basic Unit, Drive Package ~ ~

		Price USA	WT(lbs)
C185-100	Schulte FX-1800, Basic Unit	9,201.00	5,113
S000-085	Safety Light Kit (Required)	384.00	
Choose a Drive Package:			
a)	C306-705 Drive Package, CW Center, 540 RPM	4,992.00	in base
b)	C306-715 Drive Package, CW Center, 1000 RPM	4,992.00	in base

~ ~ Selection 2 ~ Choose a Hitch Option ~ ~

C185-195	Trailing Hitch, CV Style	722.00	13
Choose a CV Shaft:			
a)	340-870WG CV Shaft, 540 RPM	1124.00	74
b)	340-648WG CV Shaft, 1000 RPM	921.00	60
c)	340-658WG CV Shaft 1000 RPM 1 3/4" shaft	1,221.00	60
C185-196	Equal Angle Hitch Kit w/ 540 RPM Shaft	2,044.00	250

~ ~ Selection 3 ~ Choose a Clevis ~ ~

CS01-106WG	Open Clevis (Minimum Requirments)	128.00	11
C000-360WG	Adjustable Clevis (not required with FLX10 or FLX15)	279.00	15
C000-300WG	Precision hitch	413.00	28
C502-113WG	Solid Tongue	114.00	13

~ ~ Selection 4 ~ Choose Center and The Wing Axle Kit ~ ~

C180-115	Duals Wheel Standard on Center OR	1,124.00	237
C180-125	Walking Tandems on center (6 Tires minimum)	2,065.00	300
C180-870	Single Axle Kit for Left and Right Wings (required)	861.00	162

NOTE: (accomodates 1 or 2 tires)
Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEET



This list supersedes all previous lists.

USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-1800 Pan ROTARY CUTTER

~ ~ Selection 5 ~ Choose a Safety Guard ~ ~

C180-520	Chain Guards Single Front and Rear	606.00	206
C180-500	Chain Guards Double Front and Rear	815.00	308

~ ~ Selection 6 ~ Choose a Pan Kit ~ ~

C316-450	Pan Kit (required)	1,220.00	270
-----------------	--------------------	-----------------	-----

~ ~ Selection 7 ~ Choose a Blade Configuration ~ ~

C316-451	CW Schulte Super Suction Updraft 4" Blades	286.00	77
C316-459	CW Schulte Super Suction Updraft 5" Blades	485.00	80
C316-453	Shredder Blades, CW Center	485.00	143

~ ~ Selection 8 ~ Choose a Axle Kit ~ ~

C180-484	Axle Kit for 4 Tires	529.00	66
C180-486	Axle Kit for 6 Tires	793.00	99
C180-488	Axle Kit for 8 Tires	1,058.00	132

~ ~ Selection 9 ~ Choose a Tire Option ~ ~

Please state the quantity of tires that you would like to order as the numbers listed below are single tires and not tire kits.

210-003WG	Solid Laminated Tires, 6 x 9 x 20	200.00	70
210-175WG	Forklift Tire 6.5 x 10 - 10 ply on 2 pce 5 bolt rim	278.00	40
210-540WG	Tire 24x8-14 20 Ply Severe Duty	343.00	70
210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	496.00	

~ ~ Selection 10 ~ Choose a Destination Code ~ ~

C185-NA	North American & Australian Decal Kit	34.00	
----------------	---------------------------------------	--------------	--

Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEET



This list supersedes all previous lists.

USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2015



FX-1800 Pan ROTARY CUTTER



~ ~ Selection 11 ~ Choose Extra Options ~ ~

C185-304	Strut Mount for Flex Arm,(Factory Installed)	580.00	25
C185-305	Strut Mount for Flex Arm, (parts only)	163.00	25
C185-325	Tension Link Leveling Rod , Factory Installed	202.00	41
C185-330	Tension Link Leveling Rod , Weld on Parts only	205.00	41
C185-310	Hose Kit, independent wing-lift	163.00	10

Assembly Charge on Pan Units **300.00**

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

IMPORTANT:

- 1) Safety Chain Kit must be used at all times when moving equipment on any type of road.
- 2) OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown Object Shield Message in the Rotary Cutter Spec section in sales price book.

Prices and specifications subject to change without notice or obligation.



MASTER PRICE SHEET



This list supersedes all previous lists.

USA MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-1200 ROTARY CUTTER

CUTTER FEATURES

- 540/1000 RPM Drive
- 7 ga. Spun Formed Stump Jumpers
- Replaceable Skid Shoes
- 7 ga Single Domed Deck
- Deck Protection Rings
- Weasler Drive Lines with Self Adjusting Clutches
- Cutting Width 126" (3.20m)
- 80 Degree CV Drive
- Height Control Cylinder & Hoses
- Wing Lift Cylinders & Hoses
- S000-010 Safety Chain (1/4" gr.70 - 10000lbs cap.)
- Operator's and Parts Manual Holder
- Over Center Folding Wings
- Transport Width (max with duals on wings) 97.5" (2.47m)

more specs on brochure

~ ~ Selection 1 ~ Choose a Basic Unit, Drive Package ~ ~

		Price USA	WT(lbs)
C195-100	FX1200, Basic Unit	8,751.00	4,863
S000-085	Safety Light Kit (Required)	384.00	
DRIVE PACKAGE (choose one)			
C307-700	CW Rotation on Center, 540 RPM	3,620.00	in base
C307-710	CW Rotation on Center, 1000 RPM	3,620.00	in base

~ ~ Selection 2 ~ Choose a Hitch Option ~ ~

C185-195	Trailing Hitch, CV Style	722.00	204
Choose a CV Shaft:			
a) 340-870WG	CV Shaft, 540 RPM	1,124.00	75
b) 340-648WG	CV Shaft, 1000 RPM	921.00	220
C185-196	Equal Angle Hitch Kit w/ 540 RPM Shaft	2,044.00	250

~ ~ Selection 3 ~ Choose a Clevis ~ ~

CS01-106WG	Open Clevis (Minimum Requirments)	128.00	11
C000-360WG	Adjustable Clevis	279.00	15
C000-300WG	Precision hitch	413.00	28
C502-113WG	Solid Tongue	114.00	13

~ ~ Selection 4 ~ Choose a Wing Axle Kit ~ ~

C190-870	Wing through Axle Kit for Right Wing (required) (accommodates 1 or 2 tires)	431.00	82
C180-115	Center Through Axles	1,124.00	237
C180-125	Center Walking Wheel Axles	2,065.00	300

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

Prices and specifications subject to change without notice or obligation.

MASTER PRICE SHEET



This list supersedes all previous lists.

USA MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-1200 ROTARY CUTTER

~ ~ Selection 5 ~ Choose a Safety Guard ~ ~

		<u>Price USA</u>	<u>WT(lbs)</u>
C190-520	Chain Guards Single Front & Rear	422.00	137
C190-500	Chain Guards Double Front & Rear	563.00	205

~ ~ Selection 6 ~ Choose The Pan Kit ~ ~

C317-450	Pan Kit (required)	858.00	190
----------	--------------------	--------	-----

~ ~ Selection 7 ~ Choose a Blade Configuration ~ ~

C317-451	Updraft Blades, CW Center	198.00	70
C317-453	Shredder Blades, CW Center	308.00	115

~ ~ Selection 8 ~ Choose a Axle Kit ~ ~

C190-483	Axle Kit for 3 Tires	399.00	51
C190-485	Axle Kit for 5 Tires	660.00	84
C180-486	Axle Kit for 6 Tires	793.00	99

~ ~ Selection 9 ~ Choose a Tire Option ~ ~

Please state the quantity of tires that you would like to order as the numbers listed below are single tires and not tire kits.

210-003WG	Solid Laminated Tires, 6 x 9 x 20	200.00	70
210-175WG	Tire Assy, Forklift, 6.5 x 10 - 10 ply on 2 pce 5 bolt rim	278.00	74
210-540WG	Tire 24x8-14 20 Ply Severe Duty	343.00	70
210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	496.00	

~ ~ Selection 10 ~ Choose a Destination Code ~ ~

C195-NA	North American & Australian Decal Kit	28.00	
---------	---------------------------------------	-------	--

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER



MASTER PRICE SHEET



This list supersedes all previous lists.

USA MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017



~ ~ Selection 11 ~ Choose a Extra Options ~ ~

S000-085	Safety Light Kit	384.00	30
C185-304	Strut Mount for Flex Arm,(Factory Installed)	580.00	25
C185-305	Strut Mount for Flex Arm, (parts only)	163.00	25
C185-325	Tension Link Leveling Rod , Factory Installed	202.00	41
C185-330	Tension Link Leveling Rod , Weld on Parts only	205.00	41

Assembly Charge 200.00

PREDELIVERY SERVICE IS REQUIRED BY DEALER OR END USER

IMPORTANT:

- 2) OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown Object Shield Message in the Rotary Cutter Spec section in sales price book.



MASTER PRICE SHEETS

This list supersedes all previous lists.



USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FLX-1510 FLEX ARM

FLEX ARM FEATURES

- New heavy duty 11l x 15, 2 ply tires, load cap. Of 4000 lbs
- Cut directly in-line with the tractor or at any offset distance upto 122"
- 6000 lb capacity, 6 bolt hubs
- Spring steel bushings, induction harden pins at major pivot points
- Minimum of 3 hydraulic circuits required to operate with 15' or 10' mov
- Heavy duty 3-1/2 x 36 welded hydraulic cylinder
- Opt. 6 port selector valve kit for independent wing action or limited tractor hydraulic outlets
- Continuous power rating 200hp @ 1000rpm
- Bolt in replacement axles
- Safety light kit
- Operator's manual in holder

HOW TO ORDER: Selection 1 will give you a complete flex arm.

To receive additional options, choose from selection 2.

~ ~ Selection 1 ~ Choose a Basic Unit ~ ~

	Price USA	Wt/lbs
1) A105-000 FLX 1510 Flexarm	21,907.00	1,850

~ ~ Selection 2 ~ Extra Options ~ ~

1) A105-350 Six Port Selector Valve Kit for Independent Wing Actions with Limited Tractor Hydraulics (Fits FLX-1510)	1,320.00	25
--	-----------------	-----------

2) A105-360 Hose kit for independent wing lift- Tractors with 4 valve banks	214.00	
--	---------------	--

When choosing this opt. you will require a C306-835
(Independent Double Acting Cylinder Kit)

* C306-835 Independent Double Acting Cylinder Kit	139.00	
--	---------------	--

Assembly	300.00	
-----------------	---------------	--

IMPORTANT: OSHA, ASAE, SAE, and ANSI standards REQUIRE the use of Chain Guards, Deflectors, or Solid Skirts/Bands at all times. Schulte recommends mower be equipped with deflectors or double chain guards for all mowing purposes. Single chain guards may be used for agricultural purposes only and are specifically not recommended for highway, right-of-way, parks or greenbelt mowing. Before ordering a mower, read the Thrown ObjectShield Information Message in the Rotary Cutter Spec Section in the sales price book.

Prices and specifications subject to change without notice or obligation.

MASTER PRICE SHEET



This list supersedes all previous lists.

USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-209 Rotary Cutter

CUTTER FEATURES - ALL HITCH TYPES

- Push or pull capability
- 9ft / 3m overall width
- Cutting Height: 2" - 13" (5.1 cm - 33 cm)
- Cutting Width: 109.25" (2.78 m)
- Cutting Capacity: 3" (7.6 cm)
- Minimum Tractor HP 50 HP (37.3 kW)
- Cat. II & III 3 Point / Semi Mount Swing (13" left or right swing), Trailing Pull
- Gearbox Rating 210 hp
- Two rotor base unit common to all configuration
- Pans with Schulte Super Suction Blades
- Double Chain Front & Rear
- 7 Ga Deck
- 540 and 1000 RPM drive options

~ ~ Selection 1 ~ Choose a FX-209 Base Unit ~ ~

		Price USA	Wt/lbs
C209-100	FX-209 Base Unit	6,732.00	

~ ~ Selection 2 ~ Choose a FX-209 Non Trailing Configuration ~ ~

Choose One Mount

C209-300	3PT Mount Option	or	1,611.00
C209-360	Semi Mount Swing	or	2,773.00
C209-370	Semi Mount		1,147.00

Choose One Drive Package

C209-710	540 RPM Drive Package NON-TRAILING	or	1,290.00
C209-715	1000 RPM Drive Package NON-TRAILING		1,512.00
C209-720	Front Frame Pushing 540 RPM Drive (only to be used with		1,912.00

FM-115 or FM350 – Front mount 3pt frame Not needed with Tractor front 3pt system)

Choose One Wheel Assembly

C209-400	FX-209 Wheel Assembly Non-Trailing Standard	or	1,408.00
C209-450	FX-209 Wheel Assembly Non-Trailing Hydraulic		2,227.00

~ ~ Selection 3 ~ Choose a FX-209 Trailing Hitch Configuration ~ ~

C209-340	FX-209 Trailing Hitch		2,934.00
CS01-106WG	Open Clevis (Minimum Requirement)	or	128.00
C000-360wg	Adjustable Clevis	or	279.00
C000-300WG	Precision Hitch	or	413.00
C502-113WG	Solid Tongue		114.00

Choose One Drive Package

C209-700	540 RPM Drive Package Trailing	or	2,166.00
C209-705	1000 RPM Drive Package Trailing		2,485.00

MASTER PRICE SHEET

This list supersedes all previous lists.



USA

Effective July 2, 2017

FX-209 Rotary Cutter

~ ~ Selection 4 ~ Choose Options ~ ~

		Price USA	Wt/lbs
C209-250	BLADE PAN OPTION (Must Pick)	1,063.00	
C209-520	HALF LENGTH BELTING OPTION (Front and Back)	207.00	

~ ~ Selection 5 ~ Choose Tire Options ~ ~

(CHOOSE 2 TIRES PER UNIT)

210-003WG	Solid Laminated Tires, 6 x 9 x 20	200.00
210-540WG	Tire 24x8-14 20 Ply Severe Duty	343.00
210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	496.00
210-175WG	Forklift New, 6.5 x 10 - 10 ply rated on 2 pcs 5 bolt rim	278.00

Assembly	300.00
----------	--------

MASTER PRICE SHEET

This list supersedes all previous lists.



USA

MACHINE PRICES AND SPECIFICATIONS

Effective July 2, 2017

FX-107 Rotary Cutter

CUTTER FEATURES - ALL HITCH TYPES

- Rigid single domed 7 gauge deck construction
- Overall width: 95.5" (2.43 m)
- Cutting Height: 3" - 12 7/8" (7.6 cm - 33 cm)
- Cutting Width: 84" (2.13 m)
- Cutting Capacity: 3" (7.6 cm)
- Minimum Tractor HP 50 HP (37.3 kW)
- Cat. II & III 3 Point / Trailing Pull
- Pull type and 3 point hitching options
- Base unit common to all configurations
- 540 RPM drive
- Double Chain Front & Rear
- 7 Ga Deck
- Pull type unit has the ability to accept open clevis, solid tongue, adjustable clevis

~ ~ Selection 1 ~ Choose a Base Unit ~ ~

		Price USA	Wt/lbs
C107-100	FX-107 Base Unit	4,374.00	

~ ~ Selection 2 ~ Choose a 3 Point Option Configuration ~ ~

C107-300	3PT Mount Option <i>(if this choosen skip Trailing Hitch Option)</i>	2,532.00	
----------	--	----------	--

~ ~ Selection 3 ~ Choose a Trailing Hitch Configuration ~ ~

C107-195	Trailing Hitch	or	3,701.00
CS01-106WG	Open Clevis <i>(Minimum Requirement)</i>	or	128.00
C000-360wg	Adjustable Clevis	or	279.00
C000-300WG	Precision Hitch	or	413.00
C502-113WG	Solid Tongue		114.00

~ ~ Selection 4 ~ Blade Pan Option ~ ~

C107-250	BLADE PAN OPTION (Must Pick)	616.00	
----------	------------------------------	--------	--

~ ~ Selection 5 ~ Choose Tire Options ~ ~

(CHOOSE 2 TIRES PER UNIT)

210-003WG	Solid Laminated Tires, 6 x 9 x 20	200.00
210-540WG	Tire 24x8-14 20 Ply Severe Duty	343.00
210-540FWG	Tire 24x8-14 20 Ply Severe Duty Foam Filled	496.00
210-175WG	Forklift New, 6.5 x 10 - 10 ply rated on 2 pcs 5 bolt rim	278.00

Assembly

200.00

Prices and specifications subject to change without notice or obligation.